



Main External and Connection Dimension

CLASS 150 A1B(3)41,(3)47,(3)61,(3)67F(N.PPL).(P.R.V)

DN	(mm) Main external and connecting dimensions														WT (Kg)
	d	L	Welding	H1	H2	W	M	K	D2	D1	D	N-Φ	b	f	
2"	51	178	216	-	107	230	-	-	92	120.5	152	4-19	15.9	1.6	9.5
2 1/2"	61	190	241	-	142	400	-	-	105	139.5	178	4-19	17.5	1.6	15.0
3"	76	203	283	-	152	400	-	-	127	152.5	190	4-19	19.1	1.6	19.0
4"	102	229	305	-	178	700	-	-	157	190.5	229	8-19	23.9	1.6	33.0
5"	127	356	-	-	252	1100	-	-	186	216	254	8-22	23.9	1.6	58.0
6"	52	394	457	-	272	1100	-	-	216	241.5	279	8-22		1.6	93.0
8"	203	457	521	-	342	1500	-	-	270	298.5	343	8-22	28.6	1.6	160.0
10"	254	533	559	335	495	600	115.5	350	324	362	406	12-25	30.2	1.6	240.0
12"	305	610	635	385	580	800	171	420	381	431.8	482.6	12-25	31.8	1.6	390.0
14"	337	686	762	430	325	800	171	420	412.8	476	535	12-29	35	1.6	510.0
16"	387	162	838	470	720	800	257	400	469.9	539.5	597	16-29	36.6	1.6	750.0
20"	489	914	991	590	840	800	257	400	58.2	635	698	20-32	42.9	1.6	1190
24"	591	1067	1143	700	1050	800	150	410	692.2	749.5	813	20-35	47.8	1.6	2100

CLASS 300 A3B(3)41,(3)47,(3)67F(N.PPL).(P.R.V)

DN	(mm) Main external and connecting dimensions														WT (Kg)
	d	L	Welding	H1	H2	W	M	K	D2	D1	D	N-Φ	b	f	
2"	51	216	216	-	107	230	-	-	92	127	165	8-19	22.3	1.6	14.5
2 1/2"	61	241	241	-	142	400	-	-	105	149	190	8-22	25.4	1.6	23.5
3"	76	283	283	-	152	400	-	-	127	168	210	8-22	28.6	1.6	30.0
4"	102	305	305	-	178	700	-	-	157	200	254	8-22	31.8	1.6	55.0
5"	127	381	-	-	252	1100	-	-	186	235	279	8-22	35	1.6	81.0
6"	152	403	457	-	272	1100	-	-	216	270	318	12-22	36.5	1.6	118.0
8"	203	502	521	-	342	1500	-	-	270	330	381	12-25	41.3	1.6	200.0
10"	254	568	559	335	495	600	115.5	350	324	387.5	444	16-29	17.7	1.6	365
12"	305	648	635	385	580	800	171	420	381	451	520.8	16-32	50.8	1.6	530
14"	337	762	762	430	325	800	171	420	412.8	514.5	584.2	20-32	53.8	1.6	740
16"	387	838	838	470	720	800	257	400	469.9	571.5	647.8	20-35	57.2	1.6	1030
20"	489	991	991	590	840	800	257	400	58.2	685.8	774.8	24-35	63.5	1.6	1540
24"	591	1143	1143	700	1050	800	150	410	692.2	812.8	914.4	24-41	69.8	1.6	2600

Wenzhou Kerui Valve Industry Co., LTD

Address:

No.1 Tantou Village, Yongqiang High-tech Park, Longwan District, Wenzhou City, China

Post Code: 328024

Tel: +86-577-86928881 / +86-577-86990007

Fax: +86-577-86912312

E-mail: sale@createvalve.com / offer@createvalve.com



Main External and Connection Dimension

CLASS 600 A1B(3)41,(3)61,(3)67F(N.PPL).(P.R.V)

DN	(mm) Main external and connecting dimensions														WT (Kg)
	d	L	Welding	H1	H2	W	M	K	D2	D1	D	N-Φ	b	f	
2"	51	292	292	-	107	700	-	-	92	127	165	8-19	25.4	6.4	25
3"	51	356	356	-	169	700	-	-	127	168.5	210	8-22	25.4	6.4	25
4"	102	432	432	-	178	1100	-	-	157.2	216	273	8-25	38	6.4	76
6"	152	559	559	250	300	600	116	350	216	292	355.6	12-29	47.2	6.4	127
8"	203	660	660	294	374	800	171	400	269.8	34 .2	419.5	12-29	55.7	6.4	350
10"	254	787	787	370	445	800	171	420	324	431.8	508	16-32	63.5	6.4	660
12"	305	838	838	420	515	800	257	400	381	489	559	20-35	66.5	6.4	820
14"	337	889	889	460	550	800	257	400	413	527	603.2	20-35	69.8	6.4	1130
16"	387	991	991	505	615	800	257	400	470	603.2	686	20-39	76.2	6.4	1550
20"	489	1194	1194	630	810	800	150	410	584.2	724	818	24-44	89	6.4	2800
24"	591	1397	1397	625	1010	800	83	650	692.2	838.2	940	24-51	101.6	6.4	5300

Wenzhou Kerui Valve Industry Co., LTD

Address:

No.1 Tantou Village, Yongqiang High-tech Park, Longwan District, Wenzhou City, China

Post Code: 328024

Tel: +86-577-86928881 / +86-577-86990007

Fax: +86-577-86912312

E-mail: sale@createvalve.com / offer@createvalve.com